

That daunting forest of weeds facing you? Not so intimidating when you have the KPW4550V in your possession.

The KPW4550V turns the most complex tasks into child's play. The Kawasaki® TJ45E 45.4cc engine incorporates all of the heavy-duty components that you have come to expect from TMC, including a chrome-plated four-bolt cylinder, a dual-ringed piston, and a forged iron crankshaft to help the KPW4550V provide long lasting performance.

The shaft assembly on the KPW4550V efficiently delivers the engine's power and torque to the work surface through its 8mm solid-steel drive shaft connected to its four-bearing heavy-duty gear head and 78mm clutch drum and heavy-duty clutch assembly. A metal engine stand, a cast aluminum clutch housing with an integrated vibration

isolating rubber damper and cast aluminum handle mounts protect the KPW4550V from damage during use and transport. A looped aluminum handle (KPW4550V) or bicycle handles (KPW4550V-50) and a full two-point harness with a quick release connector are ANSI compliant, providing the user with safe and comfortable operation. An interlocking throttle lever (KPW4550V) provides an extra level of safety.

With its incredible power, heavy-duty components, and thoughtful safety features, the KPW4550V is the ideal choice for any task, especially the most complex ones.

TMC Power Equipment - Proven by Professionals.



### FEATURES & SPECIFICATIONS

#### ENGINE

Displacement (cc):	45.4
Power (net hp):	1.9
Ignition:	Solid state
Carburetor:	Diaphragm w/ purge pump

#### CLUTCH

Diameter (mm):	78
Type:	Centrifugal

#### SHAFT

Length (in):	62
Drive Shaft Type:	Solid Steel
Diameter (mm):	8
Debris Guard:	ANSI compliant plastic

#### ERGONOMICS

Handle:	Looped with ribbed rubber grip (KPW4550V) Bicycle handles (KPW4550V-50)
Shoulder Strap:	Double harness

#### EMISSIONS

Air quality compliance:	CARB Tier III/EPA Phase 2
-------------------------	---------------------------

#### GENERAL

Dimensions (in):	19.5 (W) x 11.5 (H) x 71 (L) (KPW4550V) 23.5 (W) x 18.5 (H) x 71 (L) (KPW4550V-50)
Dry weight (lbs):	18.5 (KPW4550V/KPW4550V-50)

- A powerful 45.4cc Kawasaki TJ45E engine with a dual ringed piston and a four bolt, chrome plated cylinder provides the performance and durability that professionals demand.
- A heavy duty flat foam air filtration system keeps dirt and dust out of the engine for long lasting protection.
- A solid steel 8mm drive shaft with splined ends, supported by multiple bushings and encased at the ends with high-quality, heavy-duty bearings, efficiently and forcefully transfers the engine's power and torque to the work surface with minimal vibration.
- A heavy duty gear case featuring hardened gears and four bearings provides smooth and reliable cutting head operation.
- A heavy duty 78mm centrifugal clutch securely transfers power from the engine to the shaft assembly.
- A looped aluminum handle (KPW4550V) and bicycle handles (KPW4550V-50) meeting ANSI safety standards provides safety and comfortable control and operation.
- A throttle lever with safety interlock mechanism (KPW4550V) prevents unintended acceleration.
- A debris shield meeting ANSI safety standards allows the attachment of either a cutting head or blade.

Product specifications subject to change without notice.  
Kawasaki® is a registered trademark of Kawasaki.  
© 2014 TMC Power Equipment, Inc.